

CASETE FORMAT COMPACT

Incastrabil in 60x60



Platinum



Telecomanda cu infrarosu.

-15~50°C | -15~24°C

Domeniu de functionare pt racire/incalzire.

Orificiu prevazut pentru eventual aport de aer proaspat.

Pompa de condens cu posibilitatea de a urca condensul pana la maxim 750 mm de la baza unitatii.

Wifi ready.



AUTO Restart



Anti-cold function



Auto-dezghetare.



Timer.



Mod de noapte.



Dezumidificare independenta.



Interval larg de functionare



Panou flux de aer.



Pompa condens integrata.



Racire in mediu rece



5 trepte de viteza ventilator externa

Model unitate interioara		CAS(M)I-12MF32Z		CAS(M)I-18MF32Z	
Model unitate exteriora		U(M)E-12MF32Z		U(M)E-18MF32Z	
Tip		DC inverter			
Control		Telecomanda infrarosu			
Capacitate	Racire	BTU/h	12000 (5800 – 14000)	18000(9800-19500)	
Capacitate		kW	3.5 (1.52-5.28)	5.28 (2.9-5.74)	
SEER		W/W	6.6	6.3	
Clasa de eficienta energetica			A++	A++	
Pdesignc		kW	3.5	5.3	
Capacitate	Incalzire		14000 (6050- 15750)	18000(4300-21000)	
Capacitate		kW	4.1 (1.03-5.57)	5.28(1.26-6.15)	
SCOP		W/W	4.1	4	
Clasa de eficienta energetica			A+	A+	
Pdesignh		kW	2.7	4.2	
Tol		°C	-15	-15	
Alimentare (Unitate Interioara)	V- Ph-Hz		220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	
Alimentare (Unitate Exteriora)	V- Ph-Hz		220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	
Consum Maxim	W		2000	2200	
Curent Maxim	A		8.7	10.0	
Voum aer interior (Hi/Med/Lo)	m3/h		650/530/450	680/560/500	
Nivel sunet unitate interioara (sound pressure level)	dB(A)		42/38/34	44/42/38	
Nivel sunet unitate interioara HI (sound power level)	dB(A)		56	57	
Unitate interioara	Dimensiuni nete (W x Dx H)(caseta)	mm	570x570x260	570x570x260	
	Dimensiuni nete (W x Dx H)(panel)	mm	647x647x50	647x647x50	
	Greutate Neta/Bruta (caseta)	kg	16.2/21.4	16.2/21.4	
	Greutate Neta/Bruta (panel)	kg	2.5/4.5	2.5/4.5	
Diametru teava condens	mm		ODΦ32mm	ODΦ32mm	
Interval temperatura de pe telecomanda	°C		17-30	17-30	
Compresor	Tip		ROTARY	ROTARY	
	Brand		GMCC Toshiba	GMCC Toshiba	
Debit aer unitatea exteriora			2200	2200	
Nivel sunet unitate exteriora (sound pressure level)	dB(A)		55	57	
Nivel sunet unitate exteriora (sound power level)	dB(A)		60	63	
Unitatea exteriora	Dimensiuni(WxDxH)	mm	800x333x554	800x333x554	
	Ambalaj(WxDxH)	mm	920x390x615	920x390x615	
	Greutate Neta/Bruta	Kg	34.5/37.3	35.6/38.5	
Refrigerant	Tip		R32	R32	
	Cantitate	Kg	0.72	1.15	
Presiune proiectata	MPa		4.2/1.5	4.3/1.7	
Traseu frigorific	Lichid/ Gaz	mm(inch)	Φ6.35/Φ9.52(1/4"/3/8")	Φ6.35/Φ12.7(1/4"/1/2")	
	Lungime maxima	m	15	15	
	Inaltime maxima	m	5	5	
Tempertura ambient unitate exteriora	Racire	°C	-15~50	-15~50	
	Incalzire	°C	-15~24	-15~24	